

	WMG-821EPAT	WMG-828EPAT	WMG-821GEPAT	WMG-828GEPAT
Supported modules				
SFP Gigabit Ethernet	–	●	–	●
SFP Fast Ethernet	–	●	–	●
Number of Ports				
Maximum Number of Ports	10	10	10	10
Gigabit 10/100/1000Mbps	2	–	2	–
PoE, Gigabit 10/100/1000Mbps	–	–	8	8
PoE, Fast Ethernet 10/100Mbps	8	8	–	–
SFP port 1000Mbps	–	–	–	–
SFP port 100/1000Mbps	–	2	–	2
Power Input				
24/48VDC	●	●	●	●
Power Budget	180W	180W	180W	180W
PoE Technology Supported	PoE/PoE+	PoE/PoE+	PoE/PoE+	PoE/PoE+
Enclosure & Installation				
IP rating	IP67	IP67	IP67	IP67
Connector Type	M12	M12	M12	M12
Wall mounting	●	●	●	●
Supported Operating Temperature				
-40 to 80°C	●	●	●	●
Redundancy & Back-up				
Direct-Ring	●	●	●	●
Direct-Chain	●	●	●	●
Join-Ring	●	●	●	●
Multiple Direct-Ring	●	●	●	●
STP/RSTP	●	●	●	●
MSTP	●	●	●	●
ITU-T G.8032 ERPS	●	●	●	●
Bypass Relay	●	–	●	–
Network Management				
PoE Management	●	●	●	●
IEEE 1588 PTP V2	●	●	●	●
Port Trunking/LACP	●	●	●	●
VLAN/GVRP/MVR	●	●	●	●
QoS	●	●	●	●
IGMP/MLD Snooping	●	●	●	●
DHCP Option 82	●	●	●	●
SNMP/RMON	●	●	●	●
LLDP	●	●	●	●
Port Security	●	●	●	●
IP Source Guard	●	●	●	●
ARP Inspection	●	●	●	●
Port & MAC based Authentication (IEEE 802.1X)	●	●	●	●
RADIUS / TACACS+ 3.0	●	●	●	●
ACL (Access Control Lists)	●	●	●	●
HTTPS / SSL / SSH V2	●	●	●	●
IPv6	●	●	●	●
Alarm Relay	●	●	●	●
Standards & Approvals				
CE/FCC	●	●	●	●
UL 60950-1	●	●	●	●
EN 50155	●	●	●	●
EN 50121-4	●	●	●	●
EN 61000-4-2	●	●	●	●
EN 61000-4-4	●	●	●	●